

130 Series



Swivel & Rigid Top Plate

Capacity to 400 pounds each

FEATURES

- ✓ **Design:** heavy gauge cold rolled steel, formed for strength and heat treated.
- ✓ **Dust Cap:** protects swivel raceway bearings and improves performance.
- ✓ **Finish:** bright zinc plating to resist rust and corrosion.
- ✓ **Swivel Construction:** double ball bearing with hardened raceways.
- ✓ **Axle:** Wheel sizes 3", 4" and 5" use 3/8" dia axle. Wheel sizes 6" and 8" use 1/2" diameter axle.
- ✓ **King Pin:** 1/2" steel rivet
- ✓ **Fork Leg Spacing:** 2"

CASTER OPTIONS

- ✓ **VertiLoc® Brake:** to order, add "VL" to end of model number. 
- ✓ **Swivel Grease Seal:** Includes zerk grease fitting in dust cap. To order, add "GS" to end of model number. 
- ✓ **Optional Plate Sizes:** variety of plate sizes available – consult factory.

MOUNTING OPTIONS

Top Plate Sizes (swivel & rigid): to order, add Plate Mounting Code to end of model number. (Example: 5-130-522 PLT 2)

| Mounting Code | Top Plate Size | Bolt Hole Spacing | Mounting Bolt Size |
|---------------|-----------------|----------------------------|--------------------|
| PLT 1 | 2-3/8" x 3-5/8" | 1-3/4" x 3" | 1/4" |
| PLT 2 | 2-3/8" x 3-5/8" | 1-3/4" x 3" | 5/16" |
| PLT 3 | 3-1/8" x 4-1/8" | 2-3/8" x 3-7/16" | 5/16" |
| PLT 4 | 4" x 4" | 3" x 3" | 3/8" |
| PLT 5 | 3-3/4" x 4-1/2" | 2-5/8" x 3-5/8" to 3" x 3" | 3/8" |
| PLT 7 | 3-1/2" x 3-1/2" | 2-5/8" x 2-5/8" | 9/32" |

WHEEL OPTIONS



| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Type | Bearing | Capacity (Pounds) | Swivel Caster Model Number | Rigid Caster Model Number | Approximate Weight (Pounds) | Load Height (Inches) | Swivel Radius (Inches) |
|-------------------------|----------------------|------------------------|-------------|----------------------|----------------------------|---------------------------|-----------------------------|----------------------|------------------------|
| 3 | 1 13/16 | POLYOLEFIN | ROLLER | 400 | 3-130-532 | 3-131-532 | 1-3/4 | 4 | 2 3/8 |
| 4 | 1 5/8 | CUSHION / SOLID RUBBER | PLAIN | 225 | 4-130-109 | 4-131-109 | 2-1/8 | 5 3/8 | 3 1/2 |
| | | CUSHION / SOLID RUBBER | ROLLER | 225 | 4-130-209 | 4-131-209 | 2-1/8 | | |
| | | HARD / SOLID RUBBER | PLAIN | 400 | 4-130-110 | 4-131-110 | 2-1/8 | | |
| | | HARD / SOLID RUBBER | ROLLER | 400 | 4-130-210 | 4-131-210 | 2-1/8 | | |
| | 1 1/2 | PHENOLIC | PLAIN | 400 | 4-130-121 | 4-131-121 | 2-1/8 | | |
| | | PHENOLIC | ROLLER | 400 | 4-130-221 | 4-131-221 | 2-1/8 | | |
| | | POLYOLEFIN | PLAIN | 400 | 4-130-521 | 4-131-521 | 2-1/8 | | |
| | | POLYOLEFIN | ROLLER | 400 | 4-130-522 | 4-131-522 | 2-1/8 | | |
| 5 | 1 5/8 | CUSHION / SOLID RUBBER | PLAIN | 260 | 5-130-109 | 5-131-109 | 2-3/4 | 6 1/4 | 4 |
| | | CUSHION / SOLID RUBBER | ROLLER | 260 | 5-130-209 | 5-131-209 | 2-3/4 | | |
| | | HARD / SOLID RUBBER | PLAIN | 400 | 5-130-110 | 5-131-110 | 2-1/2 | | |
| | | HARD / SOLID RUBBER | ROLLER | 400 | 5-130-210 | 5-131-210 | 2-1/2 | | |
| | 1 1/2 | PHENOLIC | PLAIN | 400 | 5-130-121 | 5-131-121 | 2-1/2 | | |
| | | PHENOLIC | ROLLER | 400 | 5-130-221 | 5-131-221 | 2-1/2 | | |
| | | POLYOLEFIN | PLAIN | 400 | 5-130-521 | 5-131-521 | 2-3/4 | | |
| | | POLYOLEFIN | ROLLER | 400 | 5-130-522 | 5-131-522 | 2-3/4 | | |
| ADVANTAGE TPR / FLAT | ROLLER | 400 | 5-130-215GF | 5-131-215GF | 2-1/8 | | | | |
| POLYLOC / GREY | ROLLER | 400 | 5-130-215G | 5-131-215G | 2-1/8 | | | | |
| POLYLOC / BLUE | ROLLER | 400 | 5-130-215P | 5-131-215P | 2-1/8 | | | | |
| 6 | 1 1/2 | PHENOLIC | PLAIN | 400 | 6-130-121 | 6-131-121 | 2-3/4 | 7 1/2 | 4 3/4 |
| | | PHENOLIC | ROLLER | 400 | 6-130-221 | 6-131-221 | 2-3/4 | | |
| | | POLYOLEFIN | DELTRIN | 400 | 6-130-523 | 6-131-523 | 2-3/4 | | |
| | | POLYOLEFIN | ROLLER | 400 | 6-130-522 | 6-131-522 | 2-3/4 | | |
| | | ADVANTAGE TPR / FLAT | ROLLER | 400 | 6-130-215GF | 6-131-215GF | 2-3/4 | | |
| | | POLYLOC / GREY | ROLLER | 400 | 6-130-215G | 6-131-215G | 2-3/4 | | |
| | | POLYLOC / BLUE | ROLLER | 400 | 6-130-215P | 6-131-215P | 2-3/4 | | |
| | | 8 | 1 1/2 | ADVANTAGE TPR / FLAT | ROLLER | 250 | 8-130-215GF | | |
| POLYLOC / GREY | ROLLER | | | 250 | 8-130-215G | 8-131-215G | 3 | | |
| POLYLOC / BLUE | ROLLER | | | 250 | 8-130-215P | 8-131-215P | 3 | | |
| POLYOLEFIN | DELTRIN | | | 250 | 8-130-523 | 8-131-523 | 3 | | |
| POLYOLEFIN | ROLLER | | | 250 | 8-130-522 | 8-131-522 | 3 | | |



5-131-215GF PLT2
(shown in photo)

5-130-522 PLT2
(shown in photo)



134 Series

Spring Ring Stem

Capacity to 400 pounds each

FEATURES

- ✓ **Design:** heavy gauge cold rolled steel, formed for strength and heat treated.
- ✓ **Dust Cap:** protects swivel raceway bearings and improves performance.
- ✓ **Finish:** bright zinc plating to resist rust and corrosion.
- ✓ **Swivel Construction:** double ball bearing with hardened raceways.
- ✓ **Axle:** Wheel sizes 3", 4" and 5" use 3/8" dia axle. Wheel sizes 6" and 8" use 1/2" diameter axle.
- ✓ **King Pin:** 1/2" steel rivet
- ✓ **Fork Leg Spacing:** 2"

CASTER OPTIONS

✓ **VertiLoc® Brake:** to order, add "VL" to end of model number.



✓ **Swivel Grease Seal:** Includes zerk grease fitting in dust cap. To order, add "GS" to end of model number.



✓ **Optional Stem Sizes:** variety of stem sizes available – consult factory.



5-134-215G STEM 1
(shown in photo)

MOUNTING OPTIONS

Standard Stem Sizes: to order, specify stem code number and add to end of caster model number (Example: 6-134-215G STEM 1).

| Stem Code | Stem Sizes |
|-----------|--------------------------------|
| STEM 1 | 3/4" diameter x 2-3/16" long |
| STEM 2 | 13/16" diameter x 2-3/16" long |
| STEM 3 | .845" diameter x 2-3/16" long |
| STEM 4 | .865" diameter x 2-3/16" long |
| STEM 5 | 1" diameter x 2-3/16" long |
| STEM 6 | .860" SQUARE x 2-3/16" long |

WHEEL OPTIONS



| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Type | Bearing | Capacity (Pounds) | Spring Ring Stem Model Number | Approximate Weight (Pounds) | Load Height (Inches) | Swivel Radius (Inches) |
|-------------------------|----------------------|------------------------|------------|-------------------|-------------------------------|-----------------------------|----------------------|------------------------|
| 3 | 1 13/16 | POLYOLEFIN | ROLLER | 400 | 3-134-532 | 1-3/4 | 3 13/16 | 2 3/8 |
| 4 | 1 5/8 | CUSHION / SOLID RUBBER | PLAIN | 225 | 4-134-109 | 2-1/8 | 5 3/16 | 3 1/2 |
| | | CUSHION / SOLID RUBBER | ROLLER | 225 | 4-134-209 | 2-1/8 | | |
| | | HARD / SOLID RUBBER | PLAIN | 400 | 4-134-110 | 2-1/8 | | |
| | | HARD / SOLID RUBBER | ROLLER | 400 | 4-134-210 | 2-1/8 | | |
| | 1 1/2 | PHENOLIC | PLAIN | 400 | 4-134-121 | 2-1/8 | | |
| | | PHENOLIC | ROLLER | 400 | 4-134-221 | 2-1/8 | | |
| | | POLYOLEFIN | PLAIN | 400 | 4-134-521 | 2-1/8 | | |
| | | POLYOLEFIN | ROLLER | 400 | 4-134-522 | 2-1/8 | | |
| 5 | 1 5/8 | CUSHION / SOLID RUBBER | PLAIN | 260 | 5-134-109 | 2-3/4 | 6 1/16 | 4 |
| | | CUSHION / SOLID RUBBER | ROLLER | 260 | 5-134-209 | 2-3/4 | | |
| | | HARD / SOLID RUBBER | PLAIN | 400 | 5-134-110 | 2-1/2 | | |
| | | HARD / SOLID RUBBER | ROLLER | 400 | 5-134-210 | 2-1/2 | | |
| | 1 1/2 | PHENOLIC | PLAIN | 400 | 5-134-121 | 2-1/2 | | |
| | | PHENOLIC | ROLLER | 400 | 5-134-221 | 2-1/2 | | |
| | | POLYOLEFIN | PLAIN | 400 | 5-134-521 | 2-3/4 | | |
| | | POLYOLEFIN | ROLLER | 400 | 5-134-522 | 2-3/4 | | |
| 6 | 1 1/2 | ADVANTAGE TPR / FLAT | ROLLER | 400 | 5-134-215GF | 2-1/8 | 7 5/16 | 4 3/4 |
| | | POLYLOC / GREY | ROLLER | 400 | 5-134-215G | 2-1/8 | | |
| | | POLYLOC / BLUE | ROLLER | 400 | 5-134-215P | 2-1/8 | | |
| | | PHENOLIC | PLAIN | 400 | 6-134-121 | 2-3/4 | | |
| | | PHENOLIC | ROLLER | 400 | 6-134-221 | 2-3/4 | | |
| | | POLYOLEFIN | DELTRIN | 400 | 6-134-523 | 2-3/4 | | |
| | | POLYOLEFIN | ROLLER | 400 | 6-134-522 | 2-3/4 | | |
| | | ADVANTAGE TPR / FLAT | ROLLER | 400 | 6-134-215GF | 2-3/4 | | |
| POLYLOC / GREY | ROLLER | 400 | 6-134-215G | 2-3/4 | | | | |
| POLYLOC / BLUE | ROLLER | 400 | 6-134-215P | 2-3/4 | | | | |
| 8 | 1 1/2 | ADVANTAGE TPR / FLAT | ROLLER | 250 | 8-134-215GF | 3 | 9 5/16 | 6 1/2 |
| | | POLYLOC / GREY | ROLLER | 250 | 8-134-215G | 3 | | |
| | | POLYLOC / BLUE | ROLLER | 250 | 8-134-215P | 3 | | |
| | | POLYOLEFIN | DELTRIN | 250 | 8-134-523 | 3 | | |
| | | POLYOLEFIN | ROLLER | 250 | 8-134-522 | 3 | | |

134 SERIES

136 Series

Threaded Stem

Capacity to 400 pounds each

FEATURES

- ✓ **Design:** heavy gauge cold rolled steel, formed for strength and heat treated.
- ✓ **Dust Cap:** protects swivel raceway bearings and improves performance.
- ✓ **Finish:** bright zinc plating to resist rust and corrosion.
- ✓ **Swivel Construction:** double ball bearing with hardened raceways.
- ✓ **Axle:** Wheel sizes 3", 4" and 5" use 3/8" dia axle. Wheel sizes 6" and 8" use 1/2" diameter axle.
- ✓ **King Pin:** 1/2" steel rivet
- ✓ **Fork Leg Spacing:** 2"

CASTER OPTIONS

✓ **VertiLoc® Brake:** to order, add "VL" to end of model number.



✓ **Swivel Grease Seal:** Includes zerk grease fitting in dust cap. To order, add "GS" to end of model number.



✓ **Optional Stem Sizes:** variety of stem sizes available – consult factory.



5-136-215GF STEM 1
(shown in photo)

MOUNTING OPTIONS

Standard Stem Sizes: to order, specify stem code number and add to end of caster model number (Example: 6-136-215G **STEM 1**).

| Stem Code | Stem Sizes |
|-----------|----------------------------------|
| STEM 1 | 1/2" diameter – 13 x 3/4" long |
| STEM 2 | 1/2" diameter – 13 x 1" long |
| STEM 3 | 1/2" diameter – 13 x 1-1/2" long |
| STEM 4 | 1/2" diameter – 20 x 3/4" long |
| STEM 5 | 1/2" diameter – 20 x 2-1/4" long |
| STEM 6 | 5/8" diameter – 11 x 1-1/4" long |
| STEM 7 | 5/8" diameter – 18 x 1-3/4" long |
| STEM 8 | 3/4" diameter – 10 x 1" long |

WHEEL OPTIONS



| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Type | Bearing | Capacity (Pounds) | Threaded Stem Model Number | Approximate Weight (Pounds) | Load Height (Inches) | Swivel Radius (Inches) |
|-------------------------|----------------------|------------------------|-------------|-------------------|----------------------------|-----------------------------|----------------------|------------------------|
| 3 | 1 13/16 | POLYOLEFIN | ROLLER | 400 | 3-136-532 | 1-3/4 | 3 7/8 | 2 3/8 |
| 4 | 1 5/8 | CUSHION / SOLID RUBBER | PLAIN | 225 | 4-136-109 | 2-1/8 | 5 3/16 | 3 1/2 |
| | | CUSHION / SOLID RUBBER | ROLLER | 225 | 4-136-209 | 2-1/8 | | |
| | | HARD / SOLID RUBBER | PLAIN | 400 | 4-136-110 | 2-1/8 | | |
| | | HARD / SOLID RUBBER | ROLLER | 400 | 4-136-210 | 2-1/8 | | |
| | 1 1/2 | PHENOLIC | PLAIN | 400 | 4-136-121 | 2-1/8 | | |
| | | PHENOLIC | ROLLER | 400 | 4-136-221 | 2-1/8 | | |
| | | POLYOLEFIN | PLAIN | 400 | 4-136-521 | 2-1/8 | | |
| | | POLYOLEFIN | ROLLER | 400 | 4-136-522 | 2-1/8 | | |
| 5 | 1 5/8 | CUSHION / SOLID RUBBER | PLAIN | 260 | 5-136-109 | 2-3/4 | 6 1/16 | 4 |
| | | CUSHION / SOLID RUBBER | ROLLER | 260 | 5-136-209 | 2-3/4 | | |
| | | HARD / SOLID RUBBER | PLAIN | 400 | 5-136-110 | 2-1/2 | | |
| | | HARD / SOLID RUBBER | ROLLER | 400 | 5-136-210 | 2-1/2 | | |
| | 1 1/2 | PHENOLIC | PLAIN | 400 | 5-136-121 | 2-1/2 | | |
| | | PHENOLIC | ROLLER | 400 | 5-136-221 | 2-1/2 | | |
| | | POLYOLEFIN | PLAIN | 400 | 5-136-521 | 2-3/4 | | |
| | | POLYOLEFIN | ROLLER | 400 | 5-136-522 | 2-3/4 | | |
| ADVANTAGE TPR / FLAT | ROLLER | 400 | 5-136-215GF | 2-1/8 | | | | |
| POLYLOC / GREY | ROLLER | 400 | 5-136-215G | 2-1/8 | | | | |
| POLYLOC / BLUE | ROLLER | 400 | 5-136-215P | 2-1/8 | | | | |
| 6 | 1 1/2 | PHENOLIC | PLAIN | 400 | 6-136-121 | 2-3/4 | 7 5/16 | 4 3/4 |
| | | PHENOLIC | ROLLER | 400 | 6-136-221 | 2-3/4 | | |
| | | POLYOLEFIN | DELTRIN | 400 | 6-136-523 | 2-3/4 | | |
| | | POLYOLEFIN | ROLLER | 400 | 6-136-522 | 2-3/4 | | |
| | | ADVANTAGE TPR / FLAT | ROLLER | 400 | 6-136-215GF | 2-3/4 | | |
| | | POLYLOC / GREY | ROLLER | 400 | 6-136-215G | 2-3/4 | | |
| | | POLYLOC / BLUE | ROLLER | 400 | 6-136-215P | 2-3/4 | | |
| 8 | 1 1/2 | ADVANTAGE TPR / FLAT | ROLLER | 250 | 8-136-215GF | 3 | 9 5/16 | 6 1/2 |
| | | POLYLOC / GREY | ROLLER | 250 | 8-136-215G | 3 | | |
| | | POLYLOC / BLUE | ROLLER | 250 | 8-136-215P | 3 | | |
| | | POLYOLEFIN | DELTRIN | 250 | 8-136-523 | 3 | | |
| | | POLYOLEFIN | ROLLER | 250 | 8-136-522 | 3 | | |